

## **RECYCLED EMBRACE LINER**

## **COLOUR FASTNESS**

Combination of colours is not recommended when the fastness values are lower than 4-5. When splicing colours with White we also recommend using a complimenting Polyester base.

COLOUR	LIGHT ISO 105 B02	RUBE ISO 10		WASHING ISO 105 C06	WATER ISO 105 E01		RATION 05 C04	SALT WATER ISO 105 E03	CHLORINE SENSITIVITY ISO 105 E03
	C.C	Dry	Wet	C.C	C.C	Acid	Alkaline	C.C	C.C
WHITE	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
SKINTONE	3-4	4	3-4	4	4	4	4	3-4	3-4
BLACK	3-4	3-4	3-4	4	4	4	4	3-4	3-4

C.C: Colour Change.

S.Co: Staining on Cotton.

S.Pa: Staining on Nylon.

S.PI: Staining on Polyester.

COLOUR FASTNESS ASSESSMENT VALUES								
LIGHT	ASSESSMENTS	OTHER TESTS	ASSESSMENTS					
1	Very Weak	1	Weak					
2	Weak	2	Limited					
3	Moderate	3	Fair					
4	Fair	4	Good					
5	Good	5	Very Good					
6	Very Good							
7	Optimal							
8	Exceptional							